


Mosaic™ Programme mechanisms









0.770.75







0 770 47



0 770 72

Selection chart for boxes, supports and plates p. 882-883

Pack	Cat.Nos	Keyswitches
		2 modules 2-position switch
1	0 770 72	By changeover contact 6 A - 250 V RONIS key no. 601 Key can be removed in both positions ○ White
1	0 770 73	3-position switch Changeover switch with OFF position 6 A - 250 V RONIS key no. 601 Key can be removed in all 3 positions ○ White
1	0 770 74	2-position switch - European key barrel 1 contact - 2 poles 6 A - 250 V Key can be removed in both positions Must be fitted with standard European key barrel or key barrel Cat.No 0 697 95 ○ White
1	0 770 75	3-position pushbutton- European key barrel Changeover switch with OFF position 6 A - 250 V Must be fitted with standard European key barrel or key barrel Cat.No 0 697 95 ○ White
1	0 697 95	European key barrel European key barrel supplied with one set of 3 keys

1	0 697 95	European key barrel supplied with o of 3 keys
		E
		Emergency stop mushroom head pushbuttons
		2 modules
1	0 766 01	With key NO + NC 3 A - 250 V Unlock with RONIS key no. 455 Red/yellow
1	0 766 02	1/4 turn NO + NC 3 A - 250 V 1/4 turn unlocking • Red/yellow

Pack Cat.Nos Keycard switches For energizing a circuit by inserting an ISO format card (e.g: Cat.No 0 767 11 or hotel room access card) Time-delay: 30 sec. after card removal Backlight insert badge area 2 modules **Electronic keycard switches** 0 784 80 Operates via contact with ISO card or key fob Cat.No 0 898 06 Communication: BUS/SCS 0 767 28 Only operates with MIFARE contactless ISO badge cards (e.g Cat.Nos 0 767 11/12/13) Contact capacity: - 110 V, power 15 VA - 230 V, power 30 VA Mechanical keycard switches 0 784 45 Operates via contact with ISO card or key fob Cat.No 089806 Contact capacity: - 110 V, power 15 VA - 230 V, power 30 VA 0 898 06 Key fob Supplied complete with a label holder for individual hotel identification

Hotel bedroom indicators Indicator lamp and bell push Enables the resident to inform hotel staff of the room status Two settings are possible: - do not disturb - please clean the room Installed in the corridor, displays calls Supplied with lamps

0 770 48

Allows the user to select the desired setting Supplied with lamp Cat.No 0 676 68 (p. 858)

Shaver socket IP 24 - IK 04

Conform to EN 60742 and EN 61558-2 Power supply 230 VA - 50/60 Hz and 1 output 120/220 V√ Connection via automatic terminals Equipped with a circuit separation transformer to

Protected against overloads and short circuits by built-in thermal relay limiting the available power to 20 VA

Insertion of the plug activates the power supply to the transformer

With integrated support

0 775 86 Supply



With integrated support
For flush mounting 2 gang boxes only,
40 mm deep
5 modules